



2455R Series Phenolic Automatic Reset Thermostats

Actual product appearance may vary.

Features

- Cost effective
- Rivet sleeve construction
- High profile
- High current

Potential Applications

- HVAC
- Automotive
- Office copy machines
- Major appliances
- Heat and smoke detectors

Description

The 2455R Series consists of a temperature-sensitive bimetal disc, electrically isolated from the switch, which actuates the normally closed contacts. The contacts open when the surface or ambient temperatures increase to the operating snap point of the calibrated disc. Response to temperature changes is extremely rapid due to the inherently low mass of the disc and the small size of the product. These products are factory calibrated to the customer's specification.

Supporting Documentation

None Available

Product Specifications	
Functional Properties	Open on rise
Reset Type	Automatic
Amperage	15 A/10 A
Voltage	120 Vac/250 Vac
Operating Temperature Range	0 °C to 150 °C [32 °F to 302 °F]
Environmental Exposure Range	-18 °C to 177 °C [0 °F to 350 °F]
Open Temperature	12.8 °C [55 °F]
Close Temperature	4.4 °C [40 °F]
Open Tolerance	2.8 °C [5 °F]
Close Tolerance	4.4 °C [8 °F]
Dielectric Strength	MIL-STD-202, Method 301; 2000 Vac 60 Hz - Terminal to Case

Insulation Resistance	MIL-STD-202, Method 302; Cond. B - 500 MOhm - 500 Vdc applied
Contact Resistance	MIL-STD-202, Method 307; 0.050 Ohm
Housing Material	Phenolic
Contact Material	Silver/nickel alloy
Approvals	UL, CSA, VDE
Mounting	No bracket
Series Name	2455R