

# TIPPMATIC®

## Manually operated Switches

### Auto-Shut-Off Rocker

#### TIPPMATIC®

Characteristics	<ul style="list-style-type: none"> <li>■ additional timer function</li> <li>■ single pole</li> <li>■ on/off</li> <li>■ illuminated/non-illum.</li> <li>■ snap-in mounting</li> <li>■ temp. 100/55°</li> </ul>
Rating	250 VAC, 12 (2) A 125 VAC, 15 A
Dimensions (mm)	37.2 × 17 × ~38
Actuator	Standard rocker 25.4 × 10.7 mm
Approvals	ENEC, cUL



### Preferred Range Switch

Ordering Reference	Illumination	Terminals 4,8	Time delay		Approvals
			50 Hz	60 Hz	
3600-411.25 1552	With	Faston 4,8 mm	18 min.	15 min.	250 VAC 12 (2) A
3600-414.25 1552	With	Faston 4,8 mm	120 min.	100 min.	250 VAC 12 (2) A

### Preferred Range Switch cover

Ordering Reference	Size (mm)	Colour
100-012.0152	10,5 × 25	white
100-012.0167	10,5 × 25	black

### Preferred Range Adapter

Ordering Reference	Size (mm)	Colour	Size	Wall thickness
100-071.0150		white	43,7 × 17,8 mm	2,5 ± 0,5 mm
100-071.0167		black	43,7 × 17,8	2,5 ± 0,5 mm

### Ordering Reference

Type	3600 TIPPMATIC®	
Illumination	With	Without
Terminals	4,8 × 0,8 mm	
Mounting	Snap-in	Customised
Rocker	White	Black
Lens	Red	Black
Housing	White	Beige
Approvals	ENEC cUL	250 VAC, 10 (2) A T100/55 125 VAC, 15 A T75

### Production range switches

Ordering Reference	Illumination	Terminals 4,8	Time delay		Approvals ENEC	cUL
			50 Hz	60 Hz		
3600-410.25 1552	With	Faston 4,8 mm	5 min.	4,1 min.	250 VAC 10 (2) A	
3600-412.25 1552	With	Faston 4,8 mm	30 min.	25 min.	250 VAC 10 (2) A	
3600-413.25 1552	With	Faston 4,8 mm	60 min.	50 min.	250 VAC 10 (2) A	
3600-419.25 1542	Without	Faston 4,8 mm	30 min.	25 min.	250 VAC 10 (2) A	
3600-420.25 1542	Without	Faston 4,8 mm	60 min.	50 min.	250 VAC 10 (2) A	
3600-510.25 1542	With	Faston 4,8 mm	5 min.	4,1 min.		125 VAC 15 A
3600-512.25 1542	With	Faston 4,8 mm	30 min.	25 min.		125 VAC 15 A
3600-513.25 1542	With	Faston 4,8 mm	60 min.	50 min.		125 VAC 15 A