



<b>Type</b>	■ Switches
<b>Product type</b>	■ th-contact Key switch for panel
<b>Dimensions</b>	■ Ø 22 mm
<b>Characteristics</b>	<ul style="list-style-type: none"> <li>■ panel cut-out 19.1 mm</li> <li>■ up to 12 contact pairs</li> <li>■ 2 security options with key actuation</li> <li>■ from 2 to 4 switch positions</li> <li>■ key trapping options</li> <li>■ solder terminals</li> </ul>
<b>Rating</b>	■ 250 VAC, 2 A
<b>Actuators</b>	■ key (common or differs)
<b>Approvals/Quality</b>	■ UL (optional)

### Typical markets

building automation & security , business machines , industrial equipment & automation , distribution

### Typical applications

alarm devices , other home security , computer peripheries , industrial automations , international catalog distributors , regional distributors , sales partners , value added distribution partners , market specific distributors

### Preferred range

Partnumber	Terminal	Actuator	Electrical rating recommended @
P23FBA206	faston 4.8 x 0.8 mm	standard key 001	250 VAC 2 (2) A -
P23FBA209	faston 4.8 x 0.8 mm	standard key 001	250 VAC 2 (2) A -
P23FBC209	faston 4.8 x 0.8 mm	standard key 001	250 VAC 2 (2) A -
P23FMA209	faston 4.8 x 0.8 mm	standard key 001, production run	250 VAC 2 (2) A -