



Type	■ Switches
Product type	■ th-contact Emergency Stop panel switch
Dimensions	<ul style="list-style-type: none"> ■ Ø 25 mm ■ Ø 30 mm ■ Ø 40 mm (on request)
Characteristics	<ul style="list-style-type: none"> ■ panel cut-out Ø 16.2/22.5 mm with adapter option ■ NC contact with 3 mm contact gap ■ rotary, reset mechanism ■ sealed IP65 ■ 1 NO + 1 NC or 2 NC
Rating	■ 250 VAC, 2 A
Actuators	■ red mushroom cap
Approvals/Quality	<ul style="list-style-type: none"> ■ EN 60947-1 ■ EN 60947-5-1 ■ EN 60947-5-5

Typical markets

business machines , building automation & security , industrial equipment & automation , healthcare & medical equipments , distribution

Typical applications

postal equipments , escalators , control panels , mobility aids , value added distribution partners , international catalog distributors

Preferred range

Partnumber	Terminal	Actuator	Electrical rating recommended @
TE180203101	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -
TE180203102	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -
TE180203201	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -
TE180203202	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -

TE180204101	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -
TE180204102	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -
TE180204201	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -
TE180204202	faston 2.8 x 0.5 (switching circuits)	-	250 VAC 2 A -
TH880200029		-	VAC A -