



<b>Type</b>	■ Switches
<b>Product type</b>	■ th-contact Emergency Stop panel switch
<b>Dimensions</b>	■ Ø 27 mm ■ Ø 40 mm
<b>Characteristics</b>	■ panel cut-out Ø 16.2/22.5 mm ■ meets EN418 directives (Ø 27 mm only) ■ sealed IP66 or IP67 ■ rotary pull or key reset ■ yellow disk bezel (optional) ■ 1 NO + 1 NC or 2 NC
<b>Rating</b>	■ 250 VAC, 6 A
<b>Actuators</b>	■ red mushroom cap (Ø 27 mm only) ■ reset by KABA key (Ø 40 mm only)
<b>Approvals/Quality</b>	■ IEC947-5-1/947-5-5 (Ø 27 mm only)

### Typical markets

business machines , heating ventilation & air conditioning , industrial equipment & automation , distribution

### Typical applications

computer peripheries , central water heating (gas- or oil-fired) , industrial automations , international catalog distributors , regional distributors , sales partners , value added distribution partners , market specific distributors

### Preferred range

Partnumber	Terminal	Actuator	Electrical rating recommended @
TE82KJB1XX	faston 2.8 x 0.5 mm	-	230 VAC 6 A -
TE81RGP2A1	faston 2.8 x 0.5 mm	-	230 VAC 6 A -