



Type	■ Switches
Product type	■ th-contact Key switch for panel
Dimensions	<ul style="list-style-type: none"> ■ 18 x 24 mm ■ 18 x 18 mm ■ Ø 18 mm ■ Ø 25 mm
Characteristics	<ul style="list-style-type: none"> ■ panel cut-out Ø 16.2/22.5 mm ■ 2 and 3 position ■ sealed IP40 or IP65 ■ wide range of plastic or aluminium bezels ■ NO, NC ■ gold plated single or double pole contact blocks ■ key trapping options
Rating	■ 250 VAC, 5 A
Actuators	■ key KABA MICRO
Approvals/Quality	<ul style="list-style-type: none"> ■ UL ■ CSA ■ VDE

Typical markets

business machines , industrial equipment & automation , defense , transportation , distribution

Typical applications

computer peripheries , industrial automations , other defense equipments , trains , international catalog distributors , regional distributors , sales partners , value added distribution partners , market specific distributors

Preferred range

Partnumber	Terminal	Actuator	Electrical rating @	
			ENEC	UL/CSA
TK21B2A001C1C1A	faston 2.8 x 0.5 mm	standard key 001	250 VAC 5 A	250 VAC 5 A
TK22B2E001C1C1E	faston 2.8 x 0.5 mm	standard key 001	250 VAC 5 A	250 VAC 5 A